

Kubota

KUBOTA FRONT MOWER

A versatile front mower with Foot-Control 4WD

F1900

Easily Engaged, Foot-Control Puts 4WD At Your Feet



The F1900's compact design provides manoeuvrability in tight corners where larger front mowers cannot go. And its range of work areas is increased with Kubota's bevel gear 4WD system. This provides a tight turning radius and delivers smooth power transfer to the wheels, even during sharp turns.

- For ground-hugging continuous traction on slopes or in slippery conditions, you can swiftly lock in 4WD on-the-go by depressing the 4WD Lock Pedal. Return to 2WD with a simple touch to the 4WD Release Pedal.
- To help you power through a tough spot, temporary "on-demand" 4WD is easy—just press and hold the two designated pedals simultaneously—the 4WD will disengage when you release the pedals.
- The F1900 is powered by a 3 cylinder, 18 horsepower, liquid cooled, Kubota diesel engine. The hydrostatic transmission eliminates shifting and clutching; speed and forward/reverse changes are controlled by the same single foot pedal.
- Two shaft driven mower decks are available: 48" and 54" side discharge mowers.
- The F1900 with 4WD has the performance features needed to get your mowing jobs done quickly and efficiently.



- 2WD F1900E model features difflock in lieu of 4WD.
- Weight of 2WD (without mower) 390kg.

*ROPS (Safety Frame) is optional

SPECIFICATIONS

MODEL	F1900
ENGINE	
Model [*]	D722
Type	Water-cooled Diesel Engine
Max. Horsepower	13.4 kW (18 HP) / 3,200 rpm
No. of Cylinders	3
Total Displacement	719 cc
Mounting	Rubber Mounting
FUEL TANK	Capacity
	Indicator
TIRE SIZE	Front
	Rear
DIMENSIONS	
Overall Length	[with 54 inch Mower Deck installed]
Overall Width	[with 54 inch Mower Deck installed]
Overall Height*	
Wheel Base	
Wheel Tread	Front
	Rear
WEIGHT (without mower)	
TRANSMISSION	
Travelling Speed	
Speed Control	
TRACTION	
STEERING	
Tilt Steering	
PTO CLUTCH	
PTO BRAKE	
MOWER DECK	
Lift System	
Driving by	
Cutting Width	
Cutting Height	
OTHERS	
Seat Adjustment	
Step Deck	
Water Temp. Meter	
Hour Meter	

*When the tilt steering is set at its highest position.
Specifications are subject to change without prior notice.

©2001 Kubota Corporation

Kubota

KUBOTA Corporation

Head Office:
2-47, Shikitsuhigashi 1-chome, Naniwa-ku, Osaka, Japan
Telex KUBOTA J65251 Fax (06) 6648-3521

NORWOOD

C. B. Norwood Distributors Limited

Head Office:
888 Tremaine Avenue
Palmerston North
New Zealand

P.O. Box 1265
Telephone (06) 356-4920
Telex 32018 Nortrac
Fax (06) 356-4939

Cat. No. 2153-01-NZ Printed in Japan. D. REX.'01-FEB.