

Kubota



KUBOTA 4WD DIESEL TRACTOR

M

M8540 Narrow Cab

With a narrow, compact body, and a new cab for operator comfort, these tractors are ideal for vineyard and orchard work.

Tend the vines and work the orchards in comfort. Kubota keeps you covered and cool.



Innovative Kubota Narrow Cab

The M8540 narrow tractor feature a newly designed, air-conditioned cab that keeps the operator comfortable while on the job. It provides ample head clearance for maximum visibility, and offers protection from heavy weather, branches, insects and more.

Air Conditioner/Heater

Whether you're trying to beat the heat on a hot summer day, or stay cozy during the chill of winter, the deluxe air conditioner/ heater puts you in charge of the climate. This advanced system maximizes airflow and optimizes cooling, heating, and air ventilation to help you work comfortably year-round, in any temperature.



Standard Equipment

- Front windshield wiper and washer
- Two front and two rear halogen work lights
- Interior dome light
- Side mirror
- Power socket for cigarette lighter
- 3-pin, 30 Amp coupler
- 7-pin trailer coupler
- Front and rear windshield wiper and washer
- CD/radio

Compact and Narrow Construction

Kubota has engineered these models specifically for those who work in vineyards, orchards or anywhere else that might require a narrow and compact tractor with M-Series power. These tractors feature an overall height of only 2260 mm and a width of just 1440mm with standard tires. The fenders have been rounded and standard, foldable hazard lights are included.



This information is sourced from overseas and may not necessarily apply locally. It is essential that you confirm specifications and other information with your local Kubota dealer.

Specifications

Model		M8540
Engine		V3800DI-TE3
Type (Make: KUBOTA)		E-CDIS, Direct Injection
No. of cylinders/Aspiration		4/Turbocharged
Engine net power	HP(kW)	85.5 (63.7)
PTO power	HP(kW)	76.0 (56.7)
Total displacement	cc	3769
Engine rpm		2600
Fuel tank capacity	ℓ	78
Alternator		60 Amp (80 Amp option)
Transmission		
No. of speeds		F15 / R15
Max. speed	km/h	37
Main gear shift (4 speeds)		Fully synchronized
Hydraulic shuttle		Standard, column-mounted lever
Main clutch type		Hydraulic multi-plate wet disc
Brake type		Hydraulic multi-plate wet discs
Mechanical differential lock		standard
4WD clutch type		Electric-hydraulic clutch
Four wheel brakes		standard
PTO		
Type		Live-independent PTO, electro-hydraulic clutch
Speed	rpm	540/540E
Hydraulics		
Pump capacity (3-Point Hitch)	ℓ/min.	61
3-Point Hitch		Rigid lower link ends
Category		II, (I)
Control system		Position, draft (top link sensing) & mixed control
Lift capacity at link end	kg	2300
Cylinder type		Two external cylinders
No. of standard remote valves		2nd (3rd valve optional)
Other features		
4WD drive system		Bevel gear type
Bi-speed turn		standard
Steering		Hydrostatic power steering
Tilt steering		Standard
Hood type		Full-open, slanted, steel
Pedal type		Hanging
Deck type (ISO-mounted)		Semi flat
Panel type		LED electronic panel w/ LCD readout (km/h & PTO speed)
Standard tyre size		
Front/Rear		280/70R18, 380/70R28
Dimensions & weight		
Overall length	mm	3680
Overall height (Front top of hood)	mm	2260
Overall width (Minimum)	mm	1440
Wheelbase	mm	2050
Crop clearance (Front Axle)	mm	380
Tread width	Front mm	1140
	Rear mm	1070-1365
Turning radius (w/o brake, w/Bi speed)	m	3.5
Tractor weight	kg	2410

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty and safety information.

©2009 Kubota Corporation

Kubota

KUBOTA Tractor Australia Pty Ltd

25-29 Permas Way, TRUGANINA Vic., 3029

Freecall: 1800 334 653

Email: sales@kubota.com.au

Web Site: <http://www.kubota.com.au>