

# **BOOMER 25C**

**ULTIMATE ALL DAY COMFORT  
2 - RANGE HYDROSTATIC TRANSMISSION  
SMALL BUT MIGHTY**





# SUB COMPACT BOOMER 25C

## 25 HP | SMALL BUT MIGHTY

The Boomer 25C sub-compact tractor is the perfect “first step” tractor for homeowners, hobby and lifestyle farmers who need a hardworking, versatile small tractor to handle the jobs other tractors can't. The economical, 25-horsepower Boomer 25C may be the smallest model in the Boomer line, but it's ready to take on your yard, farm, gardening and property maintenance jobs. Its compact size makes it easy to operate and manoeuvre around obstacles and in confined spaces.

- Ultra comfort, reversible high back seat and roomy, semi flat deck design.
- 2 - range Hydrostatic Transmission with a 450KG 3 point Hitch lift capacity and foldable ROPS.
- Safely work after dark with a lighting package that includes halogen headlights, front mounted work lights, taillights, turn signals and flashers.
- 4WD tractor comes Standard with a 4 in 1 Loader, optional Backhoe or 60" Mid - Mount mower.



# BOOMER 25C | SPECIFICATIONS

## ENGINE & FUEL

No. Cylinders / Aspiration	3 / Naturally Aspirated
Engine size	1.267
Rated Power Hp(kw)	24.7 (18.4) @3000 rpm
Max Torque @ 2100rpm (Nm)	69
Fuel Tank Capacity (litres)	25

## TRANSMISSION & AXLES

Transmission Type	Dual Pedal Hydrostatic with 2 ranges
Forward / Reverse Speed (kph @ rated rpm)	0.2 - 13.3 / 0.6 - 7.2
Cruise Control	Standard electrically activated
Rear Differential Lock Engagement / Disengagement	Standard Foot actuated Mechanical / Spring Return
4WD Engagement	Mechanical
Steering Type	Hydrostatic Power Steering

## HYDRAULIC SYSTEM

System type	Open Centre - Dual fixed displacement gear pump
Hydraulic Flow (Auxiliary / Steering)	17.1 / 8.0 LPM
High Pressure Limit (Auxiliary / Steering)	123 / 83 BAR
Auxiliary Remote Valves (rear / front)	1 / 2 + third service

## CATEGORY 1 REAR LINKAGE

Lift capacity - Maximum at ball ends	450kg
Lift capacity - Ball ends through full range	330kg

## POWER TAKE OFF (PTO)

Clutch Type	Multiplate - Wet Clutch Electro - Hydraulic engagement
PTO Speeds rpm (rear / mid)	540 / 2500

## DIMENSIONS & WEIGHT

Wheelbase 4WD (mm)	1425
Overall height to top of ROPS (folded / raised)	1628 / 2358
Turn Radius Less Brakes - 4WD Axle (mm)	2400
Total permissible weight (kg)	1175

## ACCESSORIES

Mid mount Mower deck width (mm)	1524
Front end loader capacity with 4 in 1 bucket (kg)	560
Rear mounted Backhoe max reach (mm)	2920





## CONTACT US

Blank white space for contact information.

The data indicated in this folder are approximate. The models described here can be modified without the manufacturer's notice. The drawings and photos may refer to equipment that is either optional or intended for other countries. Please get in touch with our Dealer Network for any further information. Published by CNH Industrial. Printed for New Zealand - 02/23 - NZ/1001